


Transformer:
 Combined
 50 / 100 Volt line
 5(White) : 6(Green) 50V
 5(White) : 8(Red) 100V

Secondary nominal
 tapings:
 1 : 4 6,0 W
 1 : 3 3,0 W
 2 : 4 2,0 W
 1 : 2 1,5 W
 3 : 4 0,9 W
 2 : 3 0,5 W

1W/1m Pink Noise 1/3 octave bands



Material / Colour..... ABS / RAL 9010
 Mounting..... Screws (max ø5mm)
 Termination..... Spring clamp
 Weight..... 1,4 kg
 IP-rating.....
 Max. / min. amb. temp..... 90°C / -20°C
 Standard version..... 50 / 100 V transformer
 Rated / max. power..... 6 W / 15 W
 SPL 1W/1m..... 85 dB
 SPL rated power..... 93 dB
 Effective freq. range..... 100 – 9000 Hz
 Dispersion (-6dB) 1kHz / 4kHz..... 150° / 50°
 Directivity factor, Q.....

Installation, Operation and Maintenance Procedures

- When mounting the loudspeaker please ensure that it is re-assembled in the same manner in which it was received.
- Screw the cabinet to wall or ceiling, connect cable to terminal and screw the loudspeaker grill clockwise into fixed position.
- For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated.
- BLC-550CR(T) is designed for clean room applications.
- Do not open loudspeaker when energized.
- This loudspeaker is supplied with a 2 year warranty against defective workmanship.

Most of our products are available in different colors, impedances and power ratings.

