


Transformer:
100 Volt line

Primary nominal
tappings:

1 : 2	6,0 W
2 : 3	3,0 W
3 : 4	1,5 W
1 : 3	1,0 W
2 : 4	0,5 W
1 : 4	0,3 W

1 = Red, 2 = Yellow
3 = Green, 4 = Blue

1W/1m Pink Noise 1/3 octave bands



Material / Colour..... Aluminium / RAL 9010 or anodized
 Mounting By cable as pendant
 Termination Cable, 2m
 Weight 1,8Kg
 IP-rating
 Max. / min. amb. temp 90°C / -40 °C
 Standard version 100 V transformer
 Rated / max. power 6 W / 8 W
 SPL 1W/1m..... 92 dB
 SPL rated power 99 dB
 Effective freq. range 150 – 20000 Hz
 Dispersion (-6dB) 1kHz / 4kHz 130° / 50°
 Directivity factor, Q.....

Installation, Operation and Maintenance Procedures

- When mounting the loudspeaker please ensure that the cable is fastened securely to the ceiling.
- For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated.
- Do not open loudspeaker when energized.
- This loudspeaker is supplied with a 2 year warranty against defective workmanship.

Most of our products are available in different colours, impedances and power ratings.

